

410SX VIBRATORY PLOW

 **Ditch Witch®**



VIBRATORY PLOWS

410SX VIBRATORY PLOW



1 Optional front-mounted trencher attachment features an auger for fast spoils removal.

2 When attachment or ground drive is engaged, operator-presence system stops the engine when you release the control.

3 Operator's station features easily accessible, easy-to-understand, color-coded controls; one lever controls ground speed, direction and steering.

4 Emissions-compliant engine is enclosed for quiet operation, and vibration-isolated to reduce operator fatigue.

5 Articulated-frame steering enables maneuvering around trees and other obstacles.

7 Oscillating rear axle keeps four-wheel drive engaged, for excellent traction and drawbar.

6 Vibratory plow trolley automatically centers itself when the plow blade is raised from the ground; a manual lock secures the trolley during transport.

8 49.6-gross-hp (37-kW) Kubota® gas engine provides the power you need for the most demanding conditions.



The Ditch Witch® 410SX is the most outstanding articulated-steer vibratory drop plow in its horsepower class. With dozens of innovative features, including an oscillating rear axle that keeps the machine's four-wheel drive engaged, the 410SX quickly and efficiently installs communication lines, natural gas and water services, or a complete underground sprinkler system without digging a trench. Need a trench? The 410SX can do that, too.

WE'RE IN THIS TOGETHER.



410SX VIBRATORY PLOW SPECIFICATIONS

	U.S.	METRIC
DIMENSIONS		
Height, max	63.5 in	1.61 m
Length		
W/out plow and trencher	118 in	3 m
W/plow only	151 in	3.8 m
Width, max	56 in	1.42 m
Angle of approach	21°	
Angle of departure	17°	
Wheelbase	46 in	1.17 m
Plow cover depth	26 in	660 mm
Weight		
Basic unit w/18-in blade and 36-in chain	3,910 lb	1773 kg

OPERATION		
Ground drive speed, max		
Forward	2.9 mph	4.6 km/h
Reverse	1.5 mph	2.5 km/h
Material installation diameter, max		
Pull blade	3 in	75 mm

FLUID CAPACITIES		
Fuel tank	8.5 gal	32.2 L
Hydraulic reservoir	12.7 gal	48.1 L

BATTERY		
SAE cold crank rating @ 0°F (-18°C)	800 amps	

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

	U.S.	METRIC
POWER		
Engine	Kubota® WG1605-G-E3	
Fuel	Unleaded gasoline	
Cooling medium	Liquid	
Aspiration	Natural	
Number of cylinders	4	
Displacement	93.79 in ³	1.537 L
Bore	3.11 in	79 mm
Stroke	3.09 in	78.4 mm
Manufacturer's gross power rating (per SAE J1995)	49.6 hp	37 kW
Rated speed	3,600 rpm	
Emissions compliance	EPA LSI	
Drive type		
Ground	Hydrostatic	
Plow/trencher/auxiliary	Hydraulic gear pump	
Tires, max	26 x 12-12	

HYDRAULIC SYSTEM		
Ground drive		
Pressure	4,000 psi	276 bar
Flow rate	18 gpm	68 l/min
Attachment		
Pressure	3,000 psi	207 bar
Flow rate	20.3 gpm	77 l/min
Auxiliary		
Pressure	2,000 psi	138 bar
Flow rate	8.4 gpm	31.8 l/min

VIBRATORY PLOW PARTS, ACCESSORIES AND SUPPORT:



DEALER SERVICE AND SUPPORT

Whether it's new or used equipment, parts, service, financing, or all of the above, your Ditch Witch dealer is prepared to offer you the best of everything. Ditch Witch dealers are chosen for their commitment to the underground construction profession, and they are thoroughly trained to represent the highest standards in the industry.

