

DURABLE AS THE DRILLS THAT PULL THEM.



A weak link can cripple your entire jobsite. That's why you can't skimp on important components like pullers, swivels and tabs. Ditch Witch® one-piece pullers provide a reliable connection you can count on bore after bore. Our swivels are built to last up to four times longer than aftermarket counterparts. And our pulling tabs are made from hardened steel and tested to perform up to the demanding Ditch Witch standards.

BIT PULLING ACCESSORIES



PART NUMBERS	DESCRIPTION
369-709	Bit Clevis - JT5 bits only
400-242*	Bit Pull Eye Assembly
400-2668	Pull Tool (small)
906-1828	Shackle 3/8 screw pin anchor
400-2669	Pull Tool with shackle

*See Bit Page for Application.

PULLING GRIPS

WITH SWIVEL

PART NUMBERS	SIZE
185-901	1/4 - 1/2"
185-902	1/2 - 3/4"
185-903	3/4 - 1-1/4"
185-904	1-1/4 - 2"
185-906	2 - 2-3/4"
185-907	2-3/4 - 3-1/2"
185-913	3-1/2 - 4-1/4"
185-914	4-1/4 - 4-3/4"

WITHOUT SWIVEL

PART NUMBERS	SIZE
185-917	3/4 - 1-1/4"
185-918	1-1/4 - 2"
185-919	2 - 2-3/4"
185-920	2-3/4 - 3-1/2"
185-921	3-1/2 - 4-1/4"

HEAVY-DUTY PULLING GRIP

PART NUMBERS	SIZE
185-922	3/4 - 1-1/4"
185-923	1-1/4 - 2"
185-924	2 - 2-3/4"
185-925	2-3/4 - 3-1/2"
185-926	3-1/2 - 4-1/4"



ANCHOR SHACKLES

PART NUMBERS	SIZE	BOLT SIZE	WIDTH	LOAD LIMIT
110-289	5/16"	3/8"	.53"	1K
110-509	1/2"	5/8"	.815"	4K
110-969	5/8"	3/4"	1.065"	6.5K
110-040	3/4"	7/8"	1.25"	9.5K
110-987	7/8"	1"	1.44"	13K
110-847	1"	1-1/8"	1.69"	17K
111-018	1-1/4"	1-3/8"	2.03"	24K
111-019	1-1/2"	1-5/8"	2.375"	34K
369-709	Bit Clevis	1/2"	N/A	
908-1828	3/8"	7/16"	.66"	2K

PULLERS, SWIVELS & TABS



SLEEVED PULLERS

PART NUMBERS	SIZE	MIN - MAX ID	SDR RANGE
902-2100	1"	1.050 - 1.200" ID	11 - 17
902-2200	1.25"	1.200 - 1.500" ID	9 - 17
902-2300	1.5"	1.530 - 1.620" ID	11 - 13.5
902-2400	2"	1.900 - 2.050" ID	11 - 13.5
902-2500	2.5"	2.310 - 2.700" ID	11 - 17
902-2600	3"	2.825 - 3.070" ID	11 - 17
902-2700	4"	3.620 - 4.090" ID	11 - 21
902-2800	5"	4.470 - 5.160" ID	11 - 26
902-2900	6"	5.320 - 6.040" ID	11 - 21



CARROT PULLER

Made of high-quality alloys, carrot pullers are designed for quick and reliable connections. They feature extra thread reliefs that create a clean, precise thread on the pipe to ensure a superior connection.

PART NUMBERS	SIZE	MIN - MAX ID	SDR RANGE
901-0102	.5 - 1"	0.38 - 1.08" ID	9 - 11
901-0105	1"	0.90 - 1.21" ID	7.3 - 17
901-0122	1 - 1.25"	1 - 1.39" ID	9 - 13.5
901-0125	1.25"	1.27 - 1.51" ID	9 - 17
901-0152	1.25 - 1.5"	1.1 - 1.66" ID	7 - 17
901-0150	1.5"	1.52 - 1.67" ID	11 - 17
901-0202	2.0"	1.82 - 2.10" ID	9 - 17



NON-SLEEVED PULLERS

The economical choice for trenchless installation professionals, Ditch Witch® Non-Sleeved Pullers offer the secure connection you need for pullback in tough downhole conditions. Non-sleeved pullers are made of high-quality alloys and feature a durable pulling eye for reliable performance every time. Like our sleeved puller, non-sleeved pullers can be quickly and easily installed into HDPE, PVC and other types of pipe.

PART NUMBERS	SIZE	MIN - MAX ID	SDR RANGE
902-0010	1"	1.050 - 1.200" ID	11 - 17
902-0101	1.25"	1.200 - 1.500" ID	9 - 17
902-0151	1.5"	1.530 - 1.620" ID	11 - 13.5
902-0201	2"	1.900 - 2.050" ID	11 - 13.5
902-0251	2.5"	2.310 - 2.700" ID	11 - 17
902-0301	3"	2.825 - 3.070" ID	11 - 17
902-0401	4"	3.620 - 4.090" ID	11 - 21
902-0501	5"	4.470 - 5.160" ID	11 - 26
902-0601	6"	5.320 - 6.040" ID	11 - 21
902-0801	8"	7.050 - 7.750" ID	11 - 21
902-1001	10"	8.670 - 9.875" ID	11 - 26
902-1201	12"	10.430 - 11.960" ID	11 - 23.5



SLIM LINE SWIVELS

Featuring heavy-duty contact bearings and exposed grease fittings for easy application, Ditch Witch® Slim-Line swivels are compatible with a variety of pull tabs, collars and HammerHead® pulling sleeves.

PART NUMBERS	CAPACITY
400-1588	5K Swivel
400-3056	10K Swivel
400-2744	20K Swivel
400-3059	30K Swivel



THREADED SWIVELS

PART NUMBERS	CONNECTION	CAPACITY
369-195	1.94-4F / 12K Tab	10K
400-111	1.94-4M / 12K Tab	10K
400-112	1.94-4M / 20K Tab	20K
400-236	1.94-4F / 20K Tab	20K
300-1160	1.94-4F / 30K Tab	20K
400-2558	2.38 API R M / 20K Clevis	40K
400-2559	2.38 API R M / 20K Tab	40K
400-2560	2.38 API R M / 30K Clevis	40K
400-2561	2.38 API R M / 30K Tab	40K
400-1390	3.44-4M SS / 30K Tab	40K
400-2562	2.88 API R M / 30K Clevis	60K
400-2563	2.88 API R M / 30K Tab	60K
400-2564	2.88 API R M / 40K Clevis	60K
400-2565	2.88 API R M / 40K Tab	60K
400-2566	3.5 API IF M / 40K Clevis	100K
400-2567	3.5 API IF M / 40K Tab	100K
400-2568	3.5 API IF M / 100K Clevis	100K
400-2569	3.5 API IF M / 100K Tab	100K



SLEEVED PULLER REPLACEMENT PARTS

REPLACEMENT PART	1" (25 MM) 902-2100	1.25" (32 MM) 902-2200	1.5" (40 MM) 902-2300	2" (50 MM) 902-2400	2.5" (63 MM) 902-2500	3" (75 MM) 902-2600	4" (120 MM) 902-2700	6" (160 MM) 902-2800
Stem	902-2101	902-2201	902-2301	902-2401	902-2401	902-2610	902-2610	902-2901
O-Ring Kit	902-2103	902-2203	902-2303	902-2403	902-2503	902-2603	902-2703	902-2904
Sleeve Assembly	902-2102	902-2202	902-2302	902-2402	902-2502	902-2601	902-2701	902-2902
Jaw Set	902-2114	902-2212	902-2315	902-2414	902-2513	902-2602	902-2713	902-2915
Expander Cone	902-0009	902-0109	902-0158	902-0209	902-0209	902-0302	902-0302	902-0619
Nut	n/a	n/a	n/a	n/a	n/a	2921	2921	2921
Eyebolt	30304	30304	51290	51290	51290	30291	30291	30291

PULLERS, SWIVELS & TABS



DOUBLE CLEVIS

PART NUMBERS	CONNECTION	CAPACITY
185-935	5K Clevis / 5K Clevis	10K
401-283	20K Clevis / 20K Clevis	20K
300-1164	30K Clevis / 30K Clevis	30K
401-294	100K Clevis / 100K Clevis	40K

CLEVIS TO TAB

PART NUMBERS	CONNECTION	CAPACITY
368-513	12K Clevis / 12K Tab	10K
368-634	20K Clevis / 20K Tab	20K
369-712	30K Clevis / 20K Tab	20K
300-1157	30K Clevis / 30K Tab	30K
400-748	40K Clevis / 40K Tab	60K
369-971	70K Clevis / 40K Tab	60K
369-972	100K Clevis / 70K Tab	100K



PULL TAB & PULL CLEVIS

PART NUMBERS	DESCRIPTION	MODEL(S)
369-308	1.21 M / 5K Tab	JT520
369-309	1.31 F / 5K Tab	JT520
400-1432	1.33 F / 5K Tab	JT5
368-352	1.41 M / 12K Tab	JT920 / JT920L / JT921 / JT921S / JT922
400-921	1.88 F / 10K Tab	JT1220M1
401-007	1.88 F / 20K Tab	JT1220M1
369-864	1.94 M / 10K Tab	JT920L / JT1220M1
369-865	1.94 M / 20K Tab	JT920 / JT920L / JT921 / JT921S / JT922 / JT1220M1 / JT1720M1 / JT2020M1
400-2554	2.38 API R M / 20K Tab	16K - 36K
400-2419	2.38 API R M / 30K Tab	16K - 36K
400-760	DS 2.77 M / 30K Tab	AT2720 / AT30
400-803	SS 2.77 M / 30K Tab	AT2720 / AT30 Cobble
400-2555	2.88 API R M / 30K Tab	40K - 70K
400-2518	2.88 API R M / 40K Tab	40K - 70K
401-246	3.25 M / 30K Tab	AT4020 / AT60
400-818	3.25 M / 40K Tab	AT4020 / AT60
400-820	3.25 F / 60K Tab	AT60
369-123	3.27 M / 70K Tab	JT8020M1 / JT100M1
369-122	3.27 F / 70K Tab	JT8020M1 / JT100M1
400-2556	3.5 API IF M / 40K Tab	70K - 100K
400-2519	3.5 API IF M / 100K Tab	70K - 100K
400-583	40K Socket / 30K Tab	3.5" Shaft Reamers
400-704	40K Socket / 40K Tab	JT4020M1 / AT4020
369-854	70K Clevis / 40K Tab	JT4020M1 / JT8020M1 / JT100M1 / JT60
400-781	2.77" 4 DS AT F / 30K	AT30
400-2557*	2.88 API R M / 40K Socket	40K / 60K
400-3121	2.95 M / 40K Tab	AT40

DS = Double Shoulder

SS = Single Shoulder

* Converts threaded HD reamers to 40K socket, connections and swivels.



SOCKETS

PART NUMBERS	CONNECTION	CAPACITY
300-1159	40K Socket F / 30K Tab	30K
400-221	40K Socket / 40K Tab	60K

