



# FT5

## FLUID MANAGEMENT

## KEY FEATURES/BENEFITS

### SUPPORTS SMALLER SYSTEMS

The compact FT5 makes short work of the mixing process. Designed to support smaller HDD systems, the FT5 also supports your need to get the job done right and right on time.

### FASTER MIXING

Venturi wet hopper allows excellent mixing of fluids; the hopper's steeper sides help speed up mixing cycles.

### EASIER TRANSPORT

Narrow tank can be positioned side-by-side with a drill unit on a trailer, making the equipment easy to transport to the jobsite.

### HIGH CAPACITY TANK

200-gallon (757-L) capacity is large enough to get the job done, and just the right size for transporting on small truck or trailer configurations.

### VARIETY OF SETUPS

Simplicity of design and multiple configuration options accommodate a variety of setups.

### SUPERIOR SUPPORT

Your Ditch Witch equipment is backed by a worldwide network of dealers you can count on for unmatched commitment to your success. From genuine Ditch Witch parts to factory-trained service to expert advice, your Ditch Witch dealer has it all for you.

|                          | U.S.     | METRIC |
|--------------------------|----------|--------|
| <b>DIMENSIONS</b>        |          |        |
| Length                   | 73 in    | 1.85 m |
| Length, w/hose and valve | 84 in    | 2.13 m |
| Width                    | 32 in    | 813 mm |
| Height                   | 53.5 in  | 1.36 m |
| Weight, empty            | 402 lb   | 182 kg |
| Weight, full of water    | 2,071 lb | 939 kg |

|                                     | U.S.    | METRIC   |
|-------------------------------------|---------|----------|
| <b>FLUID/MIXING SYSTEM</b>          |         |          |
| Drilling fluid/mixing tank capacity | 200 gal | 760 L    |
| Flow rate to drilling unit, max     | 18 gpm  | 68 l/min |

Specifications are general and subject to change without notice. If exact measurements are required, equipment should be weighed and measured. Due to selected options, delivered equipment may not necessarily match that shown.

|                         | U.S.                | METRIC              |
|-------------------------|---------------------|---------------------|
| <b>POWER</b>            |                     |                     |
| Engine                  | Honda® GX160        |                     |
| Fuel                    | Gasoline            |                     |
| Cooling medium          | Air                 |                     |
| Number of cylinders     | 1                   |                     |
| Displacement            | 9.9 in <sup>3</sup> | 162 cm <sup>3</sup> |
| Bore                    | 2.7 in              | 69 mm               |
| Stroke                  | 1.8 in              | 46 mm               |
| Gross power @ 3,600 rpm | 5.5 hp              | 4.1 kW              |

|                         | U.S.   | METRIC |
|-------------------------|--------|--------|
| <b>FLUID CAPACITIES</b> |        |        |
| Fuel tank               | 1 gal  | 3.6 L  |
| Engine oil              | 0.6 qt | 0.6 L  |

